

## SH30-2A Engineering Survey Drilling Rig





## Актау, Казахстан

## SH30-2A Engineering Survey Drilling Rig

1 Introduction of SH30-2A Engineering Survey Drilling Rig

SH30-2A engineering survey drilling rig is mainly used in the geological survey of placer gold exploration, industrial buildings, civil buildings, roads and bridges. The drilling rig has two feeding modes, impact and rotary, and customers can equip it on demand. Drilling rigs can be machined and customized to crawler type.

211 Features of SH30-2A Engineering Survey Drilling Rig

2.1 Simple operation and high degree of mechanization, greatly get rid of heavy manual labor.

2.2 Light weight, compact structure, good disintegration performance, removable in mountainous areas.

2.3 Equipped with a pair of rubber wheels, in flat road can be used to achieve displacement by car towing.

311 Parameters of SH30-2A Engineering Survey Drilling Rig

Model SH30-2A

Drilling capacity Open hole dia. 142mm

End hole dia. 110mm

Drill pipe dia. 42mm

Drilling depth 30m

Engine Model D180Z

Power 15hp

Winch Lifting weight max. 1500kg

Lifting speed 0.24\( \mathbb{0}.57\( \mathbb{1}\) 1.48m/s

Turntable Caliber 150mm

Speed 18 44 110r/min

Derrick Height 6m

Rubber wheels Wheel spacing 1100mm

Dimensions and weight Dimension 1780\*1010\*900

Weight 500kg

Note: Products are constantly being improved. Any changes will not be notified separately. Please refer to the actual product.

Цена: **2 500 \$** Тип объявления: Торг: уместен

Продам, продажа, продаю





**Shandong Province, China**